

contalen

PRODUCT TECHNICAL SHEET

Contalen_LD _150_2_NAT

PE LD Compound

CONTALEN 0008

Description

LDPE-Compound from LDPE packaging waste, post production waste. Recycled pellets.

General data

Application: film blowing in thickness 50-250microns

Form / shape: pellets / lenses

Filtration: 120 µm

Colour: natural

Packaging

Big Bag on non-returnable pallet
Weight app.: 1150 kg per Big Bag
Silo on request

Properties

Melt flow index
at 190°C/2.16kg (DIN ISO 1133) 1.50 (±0.30) g/10 min

Density 0.93 (±0.02) g/cm³

Bulk density ≥ 0.48 kg/dm³

Surface humidity < 1%

Our products are manufactured with the utmost care and are subject to regular quality controls. Nevertheless, slight material variations can occur.

All data stated on our product information are average values and are based on our current knowledge and experience.

They do not release the user from careful examination when applying and using our products, due to the variety of possible influences.

Legally binding commitments of certain properties for precise applications cannot be made from our stipulations. Any property rights as well as existing laws and regulations are to be observed by the receiver respectively processor of our products, on individual responsibility.

Our products are not suitable for the application in the context of the act (EC) no. 282/2008. In the following, our general conditions of sale are valid.

issued: 01.02.2016

